

The BenchTop^{PRO}
A Bioremediating Parts Washer

Quick Start/Operations Guide.

BenchtopPRO™ KIT INCLUDES:


- (1) BenchtopPRO Parts Washer
- (1) Gallon - **CONCENTRATE** Degreasing Solution
- (4) MicroPRO Packs



The BenchTopPRO is a self-contained, bioremediating parts washer with a re-circulating pump and flow-through brush.

FIRST TIME USE:

1. **UNPACK** your BenchtopPRO.
2. **OPEN** the unit by unlatching the clasp (located underneath the handle). **OPEN** the lid. **UNSNAP** the metal support leg (secured on the inside of the lid). **SWING** metal leg over the end of the lid. **SNAP** into place creating a support stand for the open lid (Diagram).
3. **REMOVE** the cardboard box from inside the sink. This box contains a (1) gallon container of **CONCENTRATE** degreasing solution and a plastic bag containing (4) MicroPRO Packs. Remove and set aside.
4. **LOCATE** the gray square structure in the BenchtopPRO sink; remove the black lid from this structure. Inside you will find the transformer/power cord/pump assembly. Connect the power cord jack to the transformer. Make sure the power cord is clear of the sink, then secure the black lid back into place.
5. **POUR** the entire (1) gallon container of **CONCENTRATE** directly into the BenchtopPRO sink.



6. **FILL** the empty **CONCENTRATE** gallon container with potable (drinking) water and **POUR** directly into the BenchtopPRO sink. **DO THIS (2) TIMES. DO NOT OVERFILL.**
Your BenchtopPRO will have a total of 3 gallons of solution when this process is complete.
7. **OPEN** one (1) MicroPRO Pack (tear package at notch) pour the entire contents of the package directly into the sink drain.
8. **CONNECT** the transformer/plug to a regular 110 volt power source/outlet. **TO TURN ON/OFF THE PUMP USE THE ROLLER SWITCH**, located on the power cord.
9. **YOU ARE NOW READY TO WASH PARTS.**

IMPORTANT INFORMATION : MICROPRO PACK MICROBES

To keep your BenchtopPRO degreasing solution clean the microbes must be fed from the grease and/or oil washed off your dirty parts at least twice a month. Upon startup add one (1) MicroPRO Pack to your BenchtopPRO, then add one (1) MicroPRO Pack every 2 weeks to maintain effectiveness. This simple action will help ensure that your unit works as intended.

ON-GOING

BenchtopPRO USE:

AS NEEDED: Top off the BenchtopPRO with BT5 degreasing solution. Pour BT5 degreasing solution directly into the sink until the fluid level reaches the bottom of the strainer basket.

USING YOUR BENCHTOPPRO LESS THAN ONCE A MONTH:

If you use your BenchtopPRO less than once a month, add two (2) MicroPRO Packs directly into the sink drain when you start your next parts cleaning job. This simple action will help ensure that your unit works as intended.

STORING IN AN UPRIGHT POSITION:
Close the lid and lock the latch. Holding the unit by the handle stand upright on level bottom.

PROPER USE FOR BenchtopPRO LID:
DO NOT WASH PARTS ON LID. Wash dirty parts in the BenchtopPRO sink.

*For More Detailed Information on the BenchtopPRO,
 For Additional Operating Instructions,
 For BenchtopPRO Videos,
 To Purchase Supplies,*

VISIT: www.thebenchtoppro.com

ORDER Supplies:
 ONLINE or By Phone:



**PRO
 BenchtopSupply Kit**

**BT5 Degreasing Solution (1 Gallon)
 MicroPRO Packs (4)**



ORDER Supplies:
 ONLINE or By Phone:




www.thebenchtoppro.com



(800) 521-7182 or (770) 564-5580

Order Supplies or Register Your Warranty Online: www.thebenchtoppro.com or (800) 521-7182

5 YEAR WARRANTY www.thebenchtoppro.com
The BenchtopPRO comes with a 5 Year Warranty on all parts including pump and brush. Shipping charges not included.

SAFETY INSTRUCTIONS:
 When using your BenchtopPRO, basic safety precautions should always be followed, including the following:
 Read ALL Instructions:

1. Care must be taken as burns can occur from touching hot parts.
2. Do not operate equipment with damaged cord or if the equipment has been dropped or damaged until it has been examined by a qualified service person.
3. Do not let a cord hang over the edge of the table, bench, or counter or come in contact with hot manifolds or moving fan blades.
4. If an extension cord is necessary, a cord with a current rating equal to or more than that of the equipment should be used. Cords rated for less current than the equipment may overheat. Care should be taken to arrange the cord so that it will not be tripped over or pulled.
5. Always unplug equipment from electrical outlet when not in use. Never use the cord to pull the plug from the outlet. Crasp plug and pull to disconnect.
6. To reduce the risk fire do not operate equipment in the vicinity of open containers of flammable liquids (gasoline).
7. Adequate ventilation should be provided when working on operating internal combustion engines.
8. Keep hair, loose clothing, fingers, and all parts of body away from moving parts.
9. To reduce the risk of electrical shock, do not use on wet surfaces or expose to rain.
10. Use only as described in this manual. Use only attachments and parts recommended by ChemFree.
11. ALWAYS WEAR SAFETY GLASSES. Everyday eyeglasses only have impact resistant lenses, they are not safety glasses.
12. It is good practice to wear gloves whenever using industrial cleaning fluids.

www.thebenchtoppro.com

INSTRUCTIONS DE SÉCURITÉ:
 Pour l'utilisation de votre BenchtopPRO, des précautions de sécurité élémentaires doivent toujours être prises, incluant ce qui suit:
 Lisez TOUTES ces Instructions :

1. Il faut faire attention car on peut se brûler en touchant des pièces chaudes.
2. Ne le faites pas fonctionner avec son cordon secteur endommagé ou si l'équipement est tombé ou a été abîmé, jusqu'à ce qu'il ait été examiné par du personnel de service qualifié.
3. Ne laissez pas le cordon pendre sur le rebord d'une table ou d'un plan de travail, ni entrer en contact avec des collecteurs chauds ou des pales de ventilateur en marche.
4. Si une extension du raccordement secteur est nécessaire, il faut utiliser une rallonge supportant le même courant ou plus que celui tiré par l'équipement, sinon il y aurait surchauffe de cette rallonge. Il faut prendre des précautions pour que le cordon ne fasse pas trébucher et ne soit pas tiré.
5. Débranchez l'équipement de la prise secteur quand il n'est pas en utilisation pendant une période longue. Ne tirez jamais sur le cordon pour débrancher sa prise de la fiche secteur. Il faut saisir directement la fiche pour la retirer.
6. Pour réduire le risque de départ d'incendie, ne faites pas fonctionner l'équipement à proximité de bidons de liquides inflammables ouverts (comme de l'essence).
7. Une ventilation adéquate doit être fournie en travaillant avec des moteurs à combustion en fonctionnement.
8. Gardez la chevelure, les vêtements lâches, les doigts et toutes les parties du corps, à l'écart de toutes les pièces mobiles.
9. Pour réduire le risque de choc électrique, n'utilisez pas l'équipement sur des surfaces mouillées ou en l'exposant à la pluie.
10. N'utilisez le manière décrite dans ce manuel. N'utilisez que des accessoires et des pièces que ChemFree recommande.
11. Portez En Permanence Des Lunettes De Sécurité. Les simples lunettes de vue n'ont que des verres résistants à l'impact.
12. C'est une bonne habitude que de porter des gants pour manier des fluides de nettoyage industriel.

www.thebenchtoppro.com

INSTRUCCIONES DE SEGURIDAD:
 Cuando use su BenchtopPRO debe observar siempre las precauciones básicas de seguridad, incluidas las siguientes:

1. Se debe tener cuidado de las quemaduras, que pueden ocurrir cuando se tocan piezas calientes.
2. No haga funcionar el cordón de alimentación eléctrica está dañado, o nado, hasta que lo examine una persona experta de servicio.
3. No deje que el cordón de alimentación eléctrica cuelgue sobre el borde de la mesa, banco o cubierla, o entre en contacto con colectores calientes o paletas móviles de ventilador.
4. Si se necesita un cordón de extensión, debe utilizarse uno con una especificación de corriente igual o mayor que el del equipo. Los cordones de alimentación eléctrica diseñados para corrientes menores que las del equipo, pueden sobrecalentarse. Se debe cuidar la disposición del cordón, para que no se pueda tropezar con él o tirar de él.
5. Desenchufe el equipo del tomacorriente eléctrico cuando no lo use por un periodo de tiempo prolongado. Nunca use el cordón para extraer el enchufe del tomacorriente. Sujete el enchufe y tire de él para desconectarlo.
6. Para reducir el riesgo de incendio, no haga funcionar el equipo en las cercanías de recipientes abiertos de líquidos inflamables (gasolina).
7. Al trabajar en motores de combustión interna en funcionamiento, debe proporcionarse una ventilación adecuada.
8. Mantenga su cabello, ropas sueltas, dedos y el resto de su cuerpo lejos de las piezas móviles.
9. Para reducir el riesgo de choque eléctrico, no use el equipo sobre superficies mojadas ni lo exponga a la lluvia.
10. Use el descrita en este manual. Use únicamente accesorios y piezas recomendadas por ChemFree.
11. Use Siempre Gafas De Seguridad. Las gafas de uso diario solo tienen lentes resistentes al impacto, y no son gafas de seguridad.
12. Es una buena práctica usar guantes toda vez que se utilicen líquidos de limpieza industriales.

www.thebenchtoppro.com

The BenchTop^{PRO}

A Bioremediating Parts Washer

PUMP MAINTENANCE:


BEFORE PERFORMING ANY MAINTENANCE ON THE PUMP, DISCONNECT FROM THE ELECTRICAL OUTLET.

To clean the pump unplug the unit from the electrical outlet. Remove the front cover. With needle nose pliers, remove the impeller. Use a small brush or stream of water to remove any debris.

(CAUTION: THE PUMP SHAFT CAN NOT BE REMOVED)

If the pump fails to operate check the following:

- Check the circuit breaker and try another outlet to ensure the pump is getting electrical power.
- Check the inlet grill to ensure it is not clogged with debris.
- Remove the front cover to access the impeller. Turn the rotor to ensure it is not broken or jammed.



ChemFree Corporation
8 Meca Way
Norcross, GA 30093 USA
770-564-5580 (P)
770-564-5533 (F)

Quick Start / Operations Guide. VISIT: www.thebenchtoppro.com